

Datum: 13.05.2025



(slika je simbolična)

## 2/2-el.mag.vent. med.,NC,vod. krm.,24VDC, G1, 0 - 6bar

Kategorija: [Solenoid valve, NC, combined operation](#)

Šifra: **102912RIE**

### Kratek opis

2/2-way solenoid valve brass, NC, force pilot operated, 24V DC, 14W, Medium temp. -10°C to 90°C, NBR+PA, G 1, PN 0 - 6bar

Economy series available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

### Tehnične Specifikacije

|                                 |                                                        |
|---------------------------------|--------------------------------------------------------|
| Min. sobna temperatura [°C]     | -10                                                    |
| Min. temperatura medija [°C]    | -10                                                    |
| Električni priključek           | For connector socket<br>Pg 9/Pg 11 acc. to<br>ISO 4400 |
| Ffunkcija                       | normally closed (NC)                                   |
| IP zaščita                      | IP 65 (with connector<br>socket fitted)                |
| Navoj                           | G 1                                                    |
| Notranji deli                   | Stainless steel                                        |
| Ohišje                          | Brass                                                  |
| Sedež ventila                   | Brass                                                  |
| Tesnilo                         | NBR                                                    |
| Max. obratovalni tlak [bar]     | 6                                                      |
| Vrsta                           | 8                                                      |
| DN                              | 25                                                     |
| A [mm]                          | 67.0                                                   |
| Max. sobna temperatura [°C]     | 80                                                     |
| Max. temperatura medija<br>[°C] | 90                                                     |
| B [mm]                          | 104.0                                                  |