

Datum: 11.05.2025



(slika je simbolična)

2/2-el.mag.vent.,NO,vod. krm.,24V DC,NBR,G2,PN0.2-10bar

Kategorija: [Solenoid valve, NO, pilot-operated](#)

Šifra: **102960RIE**

Kratek opis

2/2-way solenoid valve brass, NO, pilot operated, 24 V DC,
Medium temperature -10 °C to 90 °C, G 2, PN 0.2 - 10 bar
Economy series available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or
low-viscosity, neutral media.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-10
Min. temperatura medija [°C]	-10
Električni priključek	For connector socket Pg 9/Pg 11 acc. to ISO 4400
Ffunkcija	normally open (NO)
IP zaščita	IP 65 (with connector socket fitted)
Navoj	G 2
Notranji deli	Stainless steel
Ohišje	Brass
Sedež ventila	Brass
Tesnilo	NBR
Min. obratovalni tlak [bar]	0.2
Vrsta	6
Max. obratovalni tlak [bar]	10
DN	50
A [mm]	54.0
Max. sobna temperatura [°C]	80
Max. temperatura medija [°C]	90
B [mm]	172.0