

Datum: 01.05.2025



2/2-el.magn.ventil,NC,direkt.krm.,,230-240V,50-60Hz,G1/4,0-14bar

(slika je
simbolična)

Kategorija: [Solenoid valve, NC, directly operated](#)

Šifra: **102887RIE**

Kratek opis

2/2-way solenoid valve brass, NC, dir. operated, 230 - 240V, 50 - 60Hz, 16VA, Medium temp. -10°C to 140°C, FPM, G 1/4, PN 0-14bar

Economy series available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-10
Min. temperatura medija [°C]	-10
	For connector socket
Električni priključek	Pg 9/Pg 11 acc. to ISO 4400
Ffunkcija	normally closed (NC)
IP zaščita	IP 65 (with connector socket fitted)
Navoj	G 1/4
Notranji deli	Stainless steel
Ohišje	Brass
Sedež ventila	Brass
Tesnilo	FPM
Vrsta	2
DN	2.5
Max. obratovalni tlak [bar]	14
B [mm]	40.0
A [mm]	54.0
Max. sobna temperatura [°C]	80
Max. temperatura medija [°C]	140