

Datum: 10.05.2025



## 2/2-el.magn.ventil,NC,direkt.krm.,230V,50Hz,FPM,G1/8,PN0-18bar

(slika je  
simbolična)

Kategorija: [Solenoid valve, NC, directly operated](#)

Šifra: **102883RIE**

### Kratek opis

2/2-way solenoid valve brass, NC, directly operated, 230V, 50Hz, 10VA, Medium temp. -10°C to 140°C, FPM, G 1/8, PN 0 - 18bar

Economy series available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

### Tehnične Specifikacije

|                              |                                      |
|------------------------------|--------------------------------------|
| Min. sobna temperatura [°C]  | -10                                  |
| Min. temperatura medija [°C] | -10                                  |
|                              | For connector socket                 |
| Električni priključek        | Pg 9/Pg 11 acc. to ISO 4400          |
| Ffunkcija                    | normally closed (NC)                 |
| IP zaščita                   | IP 65 (with connector socket fitted) |
| Navoj                        | G 1/8                                |
| Notranji deli                | Stainless steel                      |
| Ohišje                       | Brass                                |
| Sedež ventila                | Brass                                |
| Tesnilo                      | FPM                                  |
| Vrsta                        | 1                                    |
| DN                           | 2.3                                  |
| Max. obratovalni tlak [bar]  | 18                                   |
| B [mm]                       | 30.0                                 |
| A [mm]                       | 41.0                                 |
| Max. sobna temperatura [°C]  | 60                                   |
| Max. temperatura medija [°C] | 140                                  |