

Datum: 02.05.2025



(slika je simbolična)

## 2/2-potni el.mag. ventil, NC, prisil. vod. krm., 230 V, 1

Kategorija: [Solenoid valve, NC, combined operation](#)

Šifra: **102839RIE**

### Kratek opis

2/2-way solenoid valve brass, NC, force pilot operated, 230 V, 50 - 60 Hz, Rp 1, NBR, Medium temp. -20 °C to 85 °C, PN 0 - 9 bar

Standard series, proven over many years, available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

### Tehnične Specifikacije

|                              |                                     |
|------------------------------|-------------------------------------|
| Min. sobna temperatura [°C]  | -20                                 |
| Min. temperatura medija [°C] | -20                                 |
| Električni priključek        | ISO 4400; cable socket (Pg 11P)     |
| Ffunkcija                    | normally closed (NC)                |
| IP zaščita                   | IP65 (with connector socket fitted) |
| Navoj                        | Rp 1                                |
| Notranji deli                | Stainless steel                     |
| Ohišje                       | Brass                               |
| Sedež ventila                | Brass                               |
| Standardni navoj             | Rp thread acc. to ISO 7-1           |
| Tesnilo                      | NBR                                 |
| Vrsta                        | 3                                   |
| Max. obratovalni tlak [bar]  | 9                                   |
| DN                           | 25                                  |
| Max. sobna temperatura [°C]  | 50                                  |
| Max. temperatura medija [°C] | 85                                  |
| A [mm]                       | 86.0                                |
| B [mm]                       | 95.0                                |