

Datum: 05.05.2025



(slika je simbolična)

2/2-potni el.mag. ventil, NC, vod. krm., 24 V DC, 2

Kategorija: [Solenoid valve, NC, pilot-operated](#)

Šifra: **102879RIE**

Kratek opis

2/2-way solenoid valve brass, NC, pilot operated, 24 V DC, Medium temperature -20 °C to 85 °C, Rp 2, PN 0.35 - 3 bar Standard series, proven over many years, available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Električni priključek	ISO 4400; cable socket (Pg 11P)
Ffunkcija	normally closed (NC)
IP zaščita	IP65 (with connector socket fitted)
Navoj	Rp 2
Notranji deli	Stainless steel
Ohišje	Brass
Sedež ventila	Brass
Standardni navoj	Rp thread acc. to ISO 7-1
Tesnilo	NBR
Min. obratovalni tlak [bar]	0.35
Max. obratovalni tlak [bar]	3
Vrsta	5
DN	44
Max. sobna temperatura [°C]	50
A [mm]	80.0
Max. temperatura medija [°C]	85
B [mm]	129.0