

Datum: 01.05.2025



(slika je simbolična)

## 2/2-potni el.mag. ventil NO, vod. krm., 24 V DC, G 3/4

Kategorija: [Solenoid valve, NO, pilot-operated, 24 V DC](#)

Šifra: **116572RIE**

### Kratek opis

2/2-way solenoid valve, Stainless steel, NO, pilot operated, 24 V DC, Medium temp. max. 80 °C / 90 °C, G 3/4, PN 0.5 - 7 bar

Standard series available in two different versions:

-Directly operated

-Pilot-operated

Connector socket, form A acc. to ISO 4400, for all valves with a G 3/8 or G 1/2 thread except valve types 3 and 4.

Special connector socket (similar to form B) for all valves with a G 1/8 or G 1/4 thread except valve types 3 and 4.

Medium temperature max. 80 °C when used with water or oils, max. 90 °C when used with air.

### Tehnične Specifikacije

|                             |                         |
|-----------------------------|-------------------------|
| IP zaščita                  | IP 65                   |
| Navoj                       | G 3/4                   |
| Notranji deli               | Stainless steel         |
| Ohišje                      | Stainless steel 1.4301  |
| Sedež ventila               | Stainless steel 1.4301  |
| Standardni navoj            | G thread acc. to DIN EN |
|                             | ISO 228-1               |
| Tesnilo                     | FPM                     |
| Min. obratovalni tlak [bar] | 0.5                     |
| Vrsta                       | 4                       |
| Max. obratovalni tlak [bar] | 7                       |
| DN                          | 20                      |
| A [mm]                      | 70.0                    |
| B [mm]                      | 82.0                    |
| C [mm]                      | 120.8                   |