

Datum: 07.05.2025



(slika je simbolična)

2/2-potni el.mag.ventil,AISI 304,NBR,NC,direkt.krm.,230 V,NPT 1/8

Kategorija: [Solenoid valve, NC, directly operated](#)

Šifra: **102969RIE**

Kratek opis

2/2-way sol. valve,AISI 304,NBR,NC,directly op.,230 V,50-60 Hz,med.temp. -25°C - 80°C,amb.temp.-25°C - 55°C,NPT 1/8,PN 0-25 bar

Available versions

- Directly operated
- Combined operation

Tehnične Specifikacije

Min. sobna temperatura [°C]	-25
Min. temperatura medija [°C]	-25
Električni priključek	For Pg 11P connector socket acc. to DIN 4400
Ffunkcija	normally closed (NC)
IP zaščita	IP65 (with connector socket fitted)
Navoj	NPT 1/8
Notranji deli	Stainless steel
Ohišje	Stainless steel 1.4301
Sedež ventila	Stainless steel 1.4301
Tesnilo	NBR
Vrsta	1
DN	2.4
Max. obratovalni tlak [bar]	25
B [mm]	30.0
Max. sobna temperatura [°C]	55
Max. temperatura medija [°C]	80
A [mm]	91.0