

Datum: 11.05.2025



(slika je simbolična)

2/2 solenoid valve, NC, G14, PN 0-16, NBR, direc. opera. 24V DC

Kategorija: [Solenoid valve, normally closed, directly operated, DC](#)

Šifra: **129303RIE**

Kratek opis

2/2-way solenoid valve, NC, Brass, G14, DN3.0, PN 0-16, NBR, directly operated 24V DC, Med.temp -20 to 85, Ambi.temp -20 to 55

In many areas, such as plant engineering, process technology or filling technology, solenoid valves are an optimum solution for control and regulation of fluids. With this professional standard series, RIEGLER offers fluid valves designed in Germany and produced in Europe. A consistently managed modular system guarantees a broad spectrum of possible valve forms in regards to sealing materials or valve bodies. If you cannot find your required specification in our standard products, please contact us.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Električni priključek	Connector socket acc. to DIN EN 175301-803 standard type A
Ffunkcija	normally closed (NC)
IP zaščita	IP 65 (bei Verwendung der Gerätesteckdose)
Navoj	G 1/4
Notranji deli	Brass and stainless steel
Ohišje	Brass
Sedež ventila	Brass and stainless steel
Standardni navoj	G thread acc. to DIN EN ISO 228-1
Tesnilo	NBR
DN	3
Max. obratovalni tlak [bar]	16
Napetost	24V DC
C [mm]	29.5
A [mm]	50.0
Max. sobna temperatura [°C]	55
B [mm]	80.0
Max. temperatura medija [°C]	85