

Datum: 30.04.2025



2/2-way solenoid valve, NO, G 1/4, PN 0-10, FPM, 110V AC

(slika je simbolična)

Kategorija: [Media-separated 2/2-way solenoid valve, NO, directly operated, AC](#)Šifra: **125785RIE**

Kratek opis

Media-separated 2/2-way solenoid valve, NO, brass, G 1/4, PN 0-10, direct. opera., 110V AC, Med.temp. 0 to 80, Amb.temp. 0 to 55

Media-separated solenoid valves are an important component in the control of fluids in systems. With these direct or pilot operated valves only the fluid housing and the separating diaphragm come into contact with the medium. Thus, these valves can withstand many different media (see resistance chart). In addition, the brass housing meets all the conventional potable water requirements. The direct controlled valve in the 3/2-way design can be used either as a mixing valve or for any desired flow direction. The pilot operated valve is normally closed in the basic position. By simply turning the 3/2-way pilot valve, the basic position can be changed to normally open.

Tehnične Specifikacije

Električni priključek	Pin terminal acc. to DIN
Ffunkcija	EN 175301-803
IP zaščita	normally open (NO)
Navoj	IP65 (with connector socket fitted)
Notranji deli	G 1/4
Ohišje	Brass
Sedež ventila	Brass
Tesnilo	Brass
DN	FPM
Max. obratovalni tlak [bar]	3
C [mm]	10
B [mm]	18.0
Max. sobna temperatura [°C]	46.0
A [mm]	55
Max. temperatura medija [°C]	71.0
Napetost	90
	110V AC