

Datum: 30.04.2025



(slika je simbolična)

3-pot. krog. ventil, L-izpust, ner.jeklo 1.4408, G11/2, DN40

Kategorija: [552](#)

Šifra: **135926RIE**

Kratek opis

3-way ball valve, L-hole, Stainless steel 1.4408, G 1 1/2, DN 40, Operating temperature -20 °C to 180 °C, PN max. 63 bar With L or T-bore, reduced bore.

Version for sealing on all sides with integrated ISO flange plate (ISO 5211).

The lever can be turned 360° to allow several switching variants.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Bore diameter padlock ISO 5211	ca. 7.9 F 07
Krogelno tesnilo	RTFE (15 % glass fibre reinforced PTFE)
Krogla	Stainless steel 1.4401
Navoj	G 1 1/2
Ohišje	Stainless steel 1.4408
Ročica	Stainless steel 1.4301, with plastic coating
Standardni navoj	G thread acc. to DIN EN ISO 228-1
Stebelno tesnilo	RTFE (15 % glass fibre reinforced PTFE)
H2 [mm]	14.3
C Ø [mm]	32.0
DN	40
Delovni tlak	63 bar (dependent on temperature)
H1 [mm]	78.3
B [mm]	120.3
L [mm]	125.8
Max. delovna temperatura [°C]	180
A [mm]	197.5