

Datum: 07.05.2025



(slika je simbolična)

3-pot. krog. ventil, T-izpust, ner.jeklo 1.4408, G 1, DN 25

Kategorija: [553](#)

Šifra: **135932RIE**

Kratek opis

3-way ball valve, T-hole, Stainless steel 1.4408, G 1, DN 25,
Operating temperature -20 °C to 180 °C, PN max. 63 bar
With L or T-bore, reduced bore.

Version for sealing on all sides with integrated ISO flange
plate (ISO 5211).

The lever can be turned 360° to allow several switching
variants.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Bore diameter padlock ISO 5211	ca. 7.9 F 05
Krogelno tesnilo	RTFE (15 % glass fibre reinforced PTFE)
Krogla	Stainless steel 1.4401
Navoj	G 1
Ohišje	Stainless steel 1.4408
Ročica	Stainless steel 1.4301, with plastic coating
Standardni navoj	G thread acc. to DIN EN ISO 228-1
Stebelno tesnilo	RTFE (15 % glass fibre reinforced PTFE)
H2 [mm]	11.0
C Ø [mm]	20.0
DN	25
H1 [mm]	56.5
Delovni tlak	63 bar (dependent on temperature)
B [mm]	93.7
L [mm]	102.4
A [mm]	136.5
Max. delovna temperatura [°C]	180