

Datum: 01.05.2025



(slika je simbolična)

## 3-potni krogelni ventil, L-izpust, nikljana medenina, Rp 1, DN 25

Kategorija: [3-way ball valve, sealing on all sides, L-bore](#)

Šifra: **103387RIE**

### Kratek opis

3-way ball valve, L-hole, nickel-plated brass, Medium / ambient temp. -15 °C to 100 °C, Rp 1, DN 25, PN max. 25 bar

The medium can enter via any of the ports to allow several switching variants.

3-way ball valves for diverting media.

### Tehnične Specifikacije

|                                       |                           |
|---------------------------------------|---------------------------|
| Min. sobna temperatura [°C]           | -15                       |
| Min. temperatura medija [°C]          | -15                       |
| Indikator položaja                    | Galvanised steel          |
| Krogla                                | Bright brass              |
| Material navojev                      | Bright brass              |
| Navoj                                 | Rp 1                      |
| Ohišje                                | Nickel-plated brass       |
| Ročica                                | Aluminium, painted black  |
| Standardni navoj                      | Rp thread acc. to ISO 7-1 |
| Tesnilo                               | PTFE / FKM                |
| Vzmet                                 | Stainless steel           |
| Bore inball                           | 23                        |
| DN                                    | 25                        |
| Max. obratovalni tlak pri 20 °C [bar] | 25                        |
| E [mm]                                | 31.0                      |
| C Ø [mm]                              | 58.0                      |
| Max. sobna temperatura [°C]           | 100                       |
| Max. temperatura medija [°C]          | 100                       |
| B [mm]                                | 102.0                     |
| L [mm]                                | 113.0                     |
| A [mm]                                | 160.0                     |