

Datum: 12.05.2025



(slika je simbolična)

3-potni krogelni ventil, nikljana medenina, L-izpust, Rp 1 1/4

Kategorija: [3-way ball valve, lower media connection, L-bore](#)

Šifra: **136331RIE**

Kratek opis

3-way ball valve, nickel-plated brass, Connection bottom, L-hole, Rp 1 1/4, DN 32, Operating temp. -15°C to 120°C, PN max. 10 bar

3-way ball valve with full throughput, integrated ISO flange plate (ISO 5211) and double-sided sealed ball.

Pressurisation is only possible via the lower connection.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-15
Krogelno tesnilo	PTFE
Krogla	Nickel-plated brass (CW617N)
Material navojev	Brass
Navoj	Rp 1 1/4
Ohišje	Nickel-plated brass (CW617N)
Ročica	Steel with plastic coating
Standardni navoj	Rp thread acc. to ISO 7-1
Stebelno tesnilo	PTFE / FKM
PN [bar]	10
E [mm]	21.4
DN	32
H1 [mm]	49.0
a/f [mm]	50
H2 [mm]	54.5
B [mm]	79.5
L [mm]	100.0
A [mm]	115.0
Max. delovna temperatura [°C]	120