

Datum: 01.05.2025



(slika je simbolična)

3-potni krogelni ventil, T-izpust, lahka izvedba, Rp 1 1/2

Kategorija: [3-way ball valves, standard type, T-bore](#)

Šifra: **103373RIE**

Kratek opis

3-way ball valve, T-hole, standard type, nickel-plated brass,
Medium/ambient temp. -15 °C to 100 °C, Rp 1 1/2, PN max.
16 bar

Sealing on all sides with T-bore.

The lever of this model can only be turned 90° rather than
360°.

Only two valve positions are therefore possible instead of
four.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-15
Min. temperatura medija [°C]	-15
Krogla	Nickel-plated brass
Material navojev	Nickel-plated brass
Navoj	Rp 1 1/2
Ohišje	Nickel-plated brass
Ročica	Aluminium, painted black
Standardni navoj	Rp thread acc. to ISO 7-1
Tesnilo	PTFE
Vzmet	Stainless steel
Max. obratovalni tlak pri 20 ° C [bar]	16
Bore inball	35
DN	40
E [mm]	40.0
C Ø [mm]	78.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
B [mm]	125.0
L [mm]	147.0
A [mm]	195.0