

Datum: 30.04.2025



(slika je simbolična)

3-potni med. krog. ventil, Pneuma. vklop, T-izpust, 1 1/4

Kategorija: [Brass ball valve, double-acting actuator, T-bore](#)

Šifra: **103561RIE**

Kratek opis

3-way brass ball valve, Pneumat. actuation drive, T-hole,
Operating temperature -20°C to 70°C, Rp 1 1/4, DN 32, PN
max. 40 bar

3-way cock, L-bore or T-bore, full bore.

Pneumatic actuators, double- or single acting version and
integrated end-position feedback.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Adapter ventila	Supplied as standard
Material krogelnega ventila	Nickel-plated brass, with ISO flange plate
Navoj	Rp 1 1/4
Pogonski material	Anodised aluminium
Položaj	T 3
Premaz za krogelni ventil	PTFE / FKM
Premaz za pogon	NBR
Različica	double-acting
Max. vodeni tlak [bar]	5.5
Priporočeni vodeni tlak [bar]	5.5
Max. vodeni tlak aktuatorja [bar]	10
DN	32
D [mm]	37.0
PN [bar]	40
a/f [mm]	55
Max. delovna temperatura [°C]	70
Kot vrtenja [°]	90
L [mm]	118.0
A [mm]	161.0
B [mm]	191.5