

Datum: 30.04.2025



(slika je simbolična)

3-potni medenina krogelni ventil, Pneumat. vklop, L-izpust, Rp 2

Kategorija: [Brass ball valve, double-acting actuator, L-bore](#)

Šifra: **103554RIE**

Kratek opis

3-way brass ball valve, Pneumat. actuation drive, L-hole,
Operating temperature -20 °C to 70 °C, Rp 2, DN 50, PN
max. 25 bar
3-way cock, L-bore or T-bore, full bore.
Pneumatic actuators, double- or single acting version and
integrated end-position feedback.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Adapter ventila	Supplied as standard
Material krogelnega ventila	Nickel-plated brass, with ISO flange plate
Navoj	Rp 2
Pogonski material	Anodised aluminium
Položaj	L 2
Premaz za krogelni ventil	PTFE / FKM
Premaz za pogon	NBR
Različica	double-acting
Priporočeni vodeni tlak [bar]	5.5
Max. vodeni tlak aktuatorja [bar]	10
PN [bar]	25
DN	50
D [mm]	56.0
a/f [mm]	67
Max. delovna temperatura [°C]	70
Kot vrtenja [°]	90
L [mm]	157.0
A [mm]	161.0
B [mm]	204.0