

Datum: 01.05.2025



3/2-5/2-potni ventil, NAMUR, G 3/8 (1), G 1/4 (3 + 5), 24 V DC

(slika je simbolična)

Kategorija: [3/2 and 5/2-way valves NAMUR](#)

Šifra: **103652RIE**

Kratek opis

3/2-5/2-way valve NAMUR, Alu, Temp. -5 °C to 50 °C,
Working pressure 1.5 - 8 bar, Connection G 3/8 (1), G 1/4 (3 + 5), 24 V DC

Pilot-operated 3/2 and 5/2-way spool valves with threaded ports and a NAMUR style interface.

Combines high-quality design with a low price.

By adding the conversion plate supplied with each valve, the device can be adapted to a 3/2-way function.

The valve is turned on by a continuous signal. Turning off causes the piston to be returned to its initial position under pressure.

Includes a manual operator as standard.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-5
Električni priključek	Connector socket PG 9 with LED display
Ohišje	Aluminium
Port 1	G 3/8
Port 3	G 1/4
Port 5	G 1/4
Ročno upravljanje	latching/non-latching
Srednje	Air, neutral gases (filtered)
Tesnilo	NBR
Min. delovni tlak [bar]	1.5
Max. delovni tlak [bar]	8
DN	10
Napetost	24 V DC
Max. delovna temperatura [°C]	50
Pretok [l/min]	1650