

Datum: 02.05.2025



3/2-potni el.mag. ventil, NC, direk. upr. 230 V, 50 - 60 Hz

(slika je simbolična)

Kategorija: [3/2-way solenoid valve, NC, directly operated](#)

Šifra: **102963RIE**

Kratek opis

3/2-way solenoid valve brass, NC, directly operated 230 V, 50 - 60 Hz, Sealing material NBR, Rp 1/8, PN 0 - 7 bar, I.D. 2.4

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Električni priključek	For Pg 11P connector socket acc. to ISO 4400
Ffunkcija	normally closed (NC)
IP zaščita	IP65 (with connector socket fitted)
Navoj	Rp 1/8
Notranji deli	Stainless steel
Ohišje	Brass
Sedež ventila	Brass
Standardni navoj	Rp thread acc. to ISO 7-1
Tesnilo	NBR
DN	2.4
Max. obratovalni tlak [bar]	7
Vrsta	7
B [mm]	30.0
A [mm]	75.0
Max. sobna temperatura [°C]	75
Max. temperatura medija [°C]	90