

Datum: 30.04.2025



(slika je simbolična)

## 3/2-potni mag. ventil s kontroliranim izpustom G 1/8 NO 6

Kategorija: [3/2-way Solenoid valve, conveyed exhaust](#)

Šifra: **106866RIE**

### Kratek opis

3/2-way solenoid valve »lineonline« controlled venting, Hose - thread, G 1/8, Hose Ø 6, NO, 24 V DC, Operating pressure 2.5-7 bar

Though small in size, these valves are solenoid-piloted and feature very high performance.

Each valve comes complete with a monostable manual control and LED. Exhaust can be damped with a silencer or conveyed via a pipe fitting.

Function corresponds to the normal position of the valve.

### Tehnične Specifikacije

|                                          |                                                            |
|------------------------------------------|------------------------------------------------------------|
| Min. temperaturno območje [°C]           | -20                                                        |
| Ffunkcija                                | NO                                                         |
| Navoj                                    | G 1/8                                                      |
| Notranji deli                            | Nickel-plated brass, brass, technopolymer, stainless steel |
| Pnevmatski simboli                       | On housing                                                 |
| Telo                                     | Technopolymer                                              |
| Tesnilo                                  | NBR                                                        |
| Vhodna moč                               | 1.2 W                                                      |
| Min. obratovalni tlak [bar]              | 2.5                                                        |
| Za cevi Ø [mm]                           | 6                                                          |
| Max. obratovalni tlak [bar]              | 7                                                          |
| I [mm]                                   | 14.6                                                       |
| Operativna napetost                      | 24 V DC                                                    |
| B [mm]                                   | 57.5                                                       |
| A [mm]                                   | 58.3                                                       |
| Max. temperaturno območje [°C]           | 60                                                         |
| Pretok pri 6,3 bar in Δp 1,0 bar [l/min] | 380                                                        |