

Datum: 01.05.2025



(slika je simbolična)

3/2-potni magnetni ventil z dušilko, G 1/4, NO, za cev 8

Kategorija: [3/2-way Solenoid valve, exhaust damped by silencer](#)Šifra: **106859RIE**

Kratek opis

3/2-way solenoid valve »lineonline« silenced venting, Hose - thread, G 1/4, Hose Ø 8, NO, 24 V DC, Operating pressure 2.5 - 7 bar

Though small in size, these valves are solenoid-piloted and feature very high performance.

Each valve comes complete with a monostable manual control and LED. Exhaust can be damped with a silencer or conveyed via a pipe fitting.

Function corresponds to the normal position of the valve.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Ffunkcija	NO
Navoj	G 1/4
Notranji deli	Nickel-plated brass, brass, technopolymer, stainless steel
Pnevmatski simboli	On housing
Telo	Technopolymer
Tesnilo	NBR
Vhodna moč	1.2 W
Min. obratovalni tlak [bar]	2.5
Max. obratovalni tlak [bar]	7
Za cevi Ø [mm]	8
l [mm]	18.7
Operativna napetost	24 V DC
Max. temperaturno območje [°C]	60
B [mm]	63.5
A [mm]	70.8
Pretok pri 6,3 bar in Δp 1,0 bar [l/min]	700