

Datum: 01.06.2025



## 3/2-preklopni vzvodni ventil, smer cevi, pot.i prik., G 1/8

(slika je simbolična)

Kategorija: [3/2-way toggle valve, pressure port on hose side](#)

Šifra: **107033RIE**

### Kratek opis

3/2-way toggle lever valve, Hose side, Push-in connector hose 8, G 1/8, PN max. 8 bar, Temp. -20 °C to 80 °C, nickel-plated brass

Manually operated toggle valve, 3/2-way types. For all applications where compressed air must be switched on or off quickly and easily or a cylinder operated manually. Designed as a banjo-type valve with a hollow bolt and ring piece. Suitable for screwing directly into the equipment or for panel mounting. Compact type of construction, also ideal where space is restricted.

### Tehnične Specifikacije

|                                |                                      |
|--------------------------------|--------------------------------------|
| Min. temperaturno območje [°C] | -20                                  |
| Navoj                          | G 1/8                                |
| Navoj za pritrditev plošče     | M12x0.75 (max. plate thickness 4 mm) |
| Nihajna roka                   | Nickel-plated brass                  |
| Notranji deli                  | Brass with a bare metal surface      |
| Povezava                       | Pressure port on hose side           |
| Preklop                        | Nickel-plated brass                  |
| Tesnilo                        | NBR                                  |
| Votli vijak                    | Nickel-plated brass                  |
| Vrsta povezave                 | Plug-in connector                    |
| Zarobljena tesnila             | Polyamide (glass fibre-reinforced)   |
| Ffunkcija                      | 3/2-way                              |
| Max. obratovalni tlak [bar]    | 8                                    |
| Za cevi [mm]                   | 8                                    |
| a/f [mm]                       | 14                                   |
| C [mm]                         | 22.5                                 |
| B [mm]                         | 55.0                                 |
| Max. temperaturno območje [°C] | 80                                   |