

Datum: 30.04.2025



(slika je simbolična)

## 3/2 ventil »FUTURA«, Elektr. voden, 115 V AC, Velikost 4, G 3/4

Kategorija: [3/2-way valve, electrically operated, 115 V AC](#)Šifra: **156614RIE**

### Kratek opis

3/2-way valve »FUTURA«, electr. actuated with solenoid 115 V AC, 50 Hz, Size 4, G 3/4, Exhaust G 1/2, Input pressure 2 - 10 bar

Pneumatic systems or parts of systems can be switched on and off by means of an electrical signal.

3/2-way type including silencer.

When they are switched off, the system is exhausted at the same time.

### Tehnične Specifikacije

|                                          |                                                       |
|------------------------------------------|-------------------------------------------------------|
| Min. temperaturno območje [°C]           | -10                                                   |
| Električni priključek                    | Socket coupling EN 175301-803, form C, poles 2+PE     |
| IP zaščita                               | IP 65                                                 |
| Izpušni zrak                             | G 1/2                                                 |
| Merjenje pretoka                         | At $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj                                    | G 3/4                                                 |
| Ohišje                                   | PA66 GF60                                             |
| Priključni navoj                         | Material: Die-cast zinc                               |
| Serijska                                 | FUTURA                                                |
| Srednje                                  | Compressed air, neutral gases                         |
| Zaklepna moč pri 50 Hz AC napetosti [VA] | 1.6                                                   |
| Min. vhodni tlak [bar]                   | 2                                                     |
| Dvižna moč pri 50 Hz AC napetosti [VA]   | 2.2                                                   |
| Vhodna moč                               | 2.5 Watt with DC voltage                              |
| Velikost                                 | 4                                                     |
| Max. vhodni tlak [bar]                   | 10                                                    |
| Max. temperaturno območje [°C]           | 50                                                    |
| A [mm]                                   | 85.0                                                  |
| Delovni cikel [%]                        | 100                                                   |
| C [mm]                                   | 110.7                                                 |
| B [mm]                                   | 177.7                                                 |
| Pretok [l/min]                           | 12500                                                 |