

Datum: 30.04.2025



(slika je simbolična)

5/2-pot.vent., enostranski el.magnet., monostab. G1/2 24VDC

Kategorija: [5/2-way spool valve, single solenoid](#)

Šifra: **106593RIE**

Kratek opis

5/2-way valve, Single-sided electromagnetic, monostable, G 1/2, 24 V DC, Operating pre. 2.5-10 bar, Operating temp. -10°C to 60°C

This valve design, featuring the Tapered Tee Seal®, offers the ability to run without lubrication and supports almost any compressed air quality.

The valves are largely resistant to dirt and can thus also be used under extreme conditions without any problems.

Leakage is now a thing of the past and the spool no longer sticks, even after long idle periods.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Delovanje	Monostable
Električni priključek	Coupler plug PG 9, form B
IP zaščita	IP 65 (DIN 46244)
Merjenje pretoka 1	Flow rate at 6 bar and ?p 1.0 bar
Ohišje	Anodised aluminium, blue
Povezava	G 1/2
Ročno upravljanje	non-latching
Tesnilo	NBR
Tuljava	Stainless steel
Min. obratovalni tlak [bar]	2.5
Min. vodeni tlak [bar]	2.5
Ffunkcija	5/2
Max. obratovalni tlak [bar]	10
DN	15
Napetost	24 V DC
Simbol	35
Max. temperaturno območje [°C]	60
Pretok 1 [l/min]	4600