

Datum: 02.05.2025



(slika je simbolična)

## **Ball valve standard type, IT/ET, nickel-plated brass, G 1 1/2**

Kategorija: [Ball valve with hand lever black, standard type, IT/ET thread](#)  
Šifra: **129138RIE**

### **Kratek opis**

Ball valve, Manual lever black, Standard type., IT/ET, nickel-plated brass, Operating temp. -20 bis 150°C, G 1 1/2, PN max. 30 bar

Applications: Compressed air, water, non-toxic and non-corrosive gases, heating systems and air conditioning systems.

### **Tehnične Specifikacije**

|                     |                                                      |
|---------------------|------------------------------------------------------|
| Delovna temperatura | -20 °C to 150 °C (no steam)                          |
| Krogelno tesnilo    | PTFE                                                 |
| Krogla              | Chrome-plated brass                                  |
| Material            | Nickel-plated brass                                  |
| Material navojev    | Nickel-plated brass                                  |
| Navoj               | G 1 1/2                                              |
| Ročica              | Galvanised steel, painted black                      |
| Standardni navoj    | G-thread acc. to DIN EN ISO 228-1, tolerance class B |
| Stebelno tesnilo    | NBR / FKM (Seal package consists of 2 O-rings)       |
| F [mm]              | 18.5                                                 |
| E [mm]              | 19.0                                                 |
| PN [bar]            | 30                                                   |
| DN                  | 40                                                   |
| B [mm]              | 81.0                                                 |
| L [mm]              | 105.5                                                |
| A [mm]              | 138.0                                                |