

Datum: 01.05.2025



(slika je simbolična)

## cev spojko, PUR, cevi Ø 12x8, dolžina 15,0 m

Kategorija: [Straight hose and DN 7.6 safety coupling](#)

Šifra: **113500RIE**

### Kratek opis

Hose coupling set, PUR, Safety coupling, Medium / ambient temperature max. 60 °C, Hose Ø 12x8, PN max. 16 bar, Length 15 m

Spiral or straight polyurethane hose, completely assembled with DN 7.6 safety coupling and steel plugs.

Coupling

Safety coupling made of steel / nickel-plated brass for high flow rates, specially designed for all applications susceptible to severe mechanical wear.

Strong, impact and vibration-resistant design for demanding environments.

Polyurethane hose

Extremely flexible spiral hose with excellent kink resistance and insensitive to dirt.

Combines high tear, tensile and impact strength with a long service life and optimal ageing qualities.

This hose is additionally characterised by outstanding resistance to abrasion and resistance to UV.

Not suitable for direct attachment to pulsating tools.

We recommend using our vibration dampers, according to ISO 6150 § 7.1.

### Tehnične Specifikacije

|                              |                    |
|------------------------------|--------------------|
| Min. sobna temperatura [°C]  | -20                |
| Min. temperatura medija [°C] | -20                |
| Material                     | Polyurethane (PUR) |
| Velikost cevi [mm]           | 12x8               |
| Storitev dolžina max. [m]    | 15.0               |
| Max. obratovalni tlak [bar]  | 16                 |
| Max. sobna temperatura [°C]  | 60                 |
| Max. temperatura medija [°C] | 60                 |