

Datum: 30.04.2025



(slika je simbolična)

## Cilinder kratkega hoda, delujoč v dveh smerehbat Ø 12hod 40M5

Kategorija: [Short-stroke cylinders, double acting, magnetic](#)

Šifra: **105900RIE**

### Kratek opis

Short stroke cylinder, double-acting, Magnet, Piston Ø 12, Stroke 40, M5, Working pressure max. 10 bar, Temp. -10 °C to 80 °C

Suitable for installation in limited spaces.

Supplied with magnet.

Suitable for filtered compressed air, lubricated (ensure continuity) or unlubricated.

### Tehnične Specifikacije

|                                |                                        |
|--------------------------------|----------------------------------------|
| Min. temperaturno območje [°C] | -10                                    |
| Bat                            | Synthetic (acetal) resin               |
| Batnica                        | C45 steel, hard chrome-plated          |
| Batnica IT                     | M3                                     |
| Cushioning                     | non-cushioned                          |
| Ffunkcija                      | double-acting                          |
| Gewinde Kolbenstange           | female piston rod                      |
| Glava                          | Painted brass                          |
| Magnet                         | with magnet                            |
| Ovoj                           | C45 steel, hard chrome-plated          |
| Povezava                       | M5                                     |
| Tesnilo batnice                | NBR (additional charge for PU and FKM) |
| Min. nastavljeni tlak [bar]    | 0.6                                    |
| Max. delovni tlak [bar]        | 10                                     |
| Bat Ø [mm]                     | 12                                     |
| Stroke [mm]                    | 40                                     |
| Max. temperaturno območje [°C] | 80                                     |