

Datum: 24.05.2025



(slika je simbolična)

Cilinder kratkega hoda, enosmerni, batØ 25, hod 25, G 1/8

Kategorija: [Short-stroke cylinders, single-acting, magnetic](#)

Šifra: **105959RIE**

Kratek opis

Short stroke cylinder, single-acting, Magnet, Piston Ø 25, Stroke 25, G 1/8, Working pressure max. 10 bar, Temp. -10 °C to 80 °C

Suitable for installation in limited spaces.

Supplied with magnet.

Suitable for filtered compressed air, lubricated (ensure continuity) or unlubricated.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Bat	Synthetic (acetal) resin
Batnica	C45 steel, hard chrome-plated
Batnica IT	M5
Cushioning	non-cushioned
Ffunkcija	single-acting
Gewinde Kolbenstange	female piston rod
Glava	Painted brass
Magnet	with magnet
Ovoj	C45 steel, hard chrome-plated
Povezava	G 1/8
Starting position	pressureless in the retracted position
Tesnilo batnice	NBR (additional charge for PU and FKM)
Min. nastavljeni tlak [bar]	0.6
Max. delovni tlak [bar]	10
Bat Ø [mm]	25
Stroke [mm]	25
Max. temperaturno območje [°C]	80