

Datum: 12.05.2025



(slika je simbolična)

Cilinder kratkega hodadelujoč v dveh smerehbatØ 63hod 30G 1/8

Kategorija: [Short-stroke cylinders, double acting, magnetic](#)
Šifra: **105940RIE**

Kratek opis

Short stroke cylinder, double-acting, Magnet, Piston Ø 63, Stroke 30, G 1/8, Working pressure max. 10 bar, Temp. -10 °C to 80 °C
Suitable for installation in limited spaces.
Supplied with magnet.
Suitable for filtered compressed air, lubricated (ensure continuity) or unlubricated.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Bat	Synthetic (acetal) resin
Batnica	C45 steel, hard chrome-plated
Batnica IT	M8
Cushioning	non-cushioned
Ffunkcija	double-acting
Gewinde Kolbenstange	female piston rod
Glava	Aluminium
Magnet	with magnet
Ovoj	C45 steel, hard chrome-plated
Povezava	G 1/8
Tesnilo batnice	NBR (additional charge for PU and FKM)
Min. nastavljeni tlak [bar]	0.4
Max. delovni tlak [bar]	10
Stroke [mm]	30
Bat Ø [mm]	63
Max. temperaturno območje [°C]	80