

Datum: 01.05.2025



(slika je simbolična)

Cilinder kratkega hodadelujoč v dveh smerehbatØ 80hod 30G 1/4

Kategorija: [Short-stroke cylinders, double acting, magnetic](#)

Šifra: **105947RIE**

Kratek opis

Short stroke cylinder, double-acting, Magnet, Piston Ø 80, Stroke 30, G 1/4, Working pressure max. 10 bar, Temp. -10 °C to 80 °C

Suitable for installation in limited spaces.

Supplied with magnet.

Suitable for filtered compressed air, lubricated (ensure continuity) or unlubricated.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Bat	Aluminium/PTFE
Batnica	C45 steel, hard chrome-plated
Batnica IT	M10
Cushioning	non-cushioned
Ffunkcija	double-acting
Gewinde Kolbenstange	female piston rod
Glava	Aluminium
Magnet	with magnet
Ovoj	C45 steel, hard chrome-plated
Povezava	G 1/4
Tesnilo batnice	NBR (additional charge for PU and FKM)
Min. nastavljeni tlak [bar]	0.4
Max. delovni tlak [bar]	10
Stroke [mm]	30
Bat Ø [mm]	80
Max. temperaturno območje [°C]	80