

Datum: 13.05.2025



(slika je simbolična)

## Cilinder s kratkim hodom del. v dveh smereh bat Ø 25hod 40M5x0,8

Kategorija: [Short-stroke cylinder, double-acting, with magnet](#)

Šifra: **115088RIE**

### Kratek opis

Short stroke cylinder »ACQ« double-acting, Magnet, Piston Ø 25, Stroke 40, M5x0,8, Working pressure 1-10 bar, Temp.

-20°C to 70°C

Suitable for installation in limited spaces.

Supplied with magnet.

Short-stroke cylinders in two different versions:

»ACQ« Series, double-acting, Ø 12 to 100

»ASQ« Series, single-acting, Ø 12 to 63

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

### Tehnične Specifikacije

|                                |                      |
|--------------------------------|----------------------|
| Min. temperaturno območje [°C] | -20                  |
| Bat                            | Aluminium            |
| Batnica                        | Steel, thick-chromed |
| Batnica IT                     | M6x1.0               |
| Cushioning                     | non-cushioned        |
| Ffunkcija                      | double-acting        |
| Gewinde Kolbenstange           | female piston rod    |
| Magnet                         | with magnet          |
| Ovoj                           | Aluminium            |
| Povezava                       | M5x0.8               |
| Serijska                       | ACQ series           |
| Tesnilo                        | NBR                  |
| Min. delovni tlak [bar]        | 1                    |
| Vrsta                          | 2                    |
| Max. delovni tlak [bar]        | 10                   |
| Batnica Ø [mm]                 | 12                   |
| Bat Ø [mm]                     | 25                   |
| Stroke [mm]                    | 40                   |
| Max. temperaturno območje [°C] | 70                   |