

Datum: 30.04.2025



(slika je simbolična)

Cilinder z kratkim hodom, enosmerni, bat Ø 12, hod 10, M5x0,8

Kategorija: [Short-stroke cylinder, single-acting, with magnet](#)

Šifra: **115167RIE**

Kratek opis

Short stroke cylinder »ASQ« single-acting, Magnet, Piston Ø 12, Stroke 10, M5x0,8, Working pressure 2-10 bar, Temp. -20°C to 70°C

Suitable for installation in limited spaces.

Supplied with magnet.

Short-stroke cylinders in two different versions:

»ACQ« Series, double-acting, Ø 12 to 100

»ASQ« Series, single-acting, Ø 12 to 63

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Messing
Batnica	Steel, thick-chromed
Batnica IT	M3x0.5
Cushioning	non-cushioned
Ffunkcija	single-acting
Gewinde Kolbenstange	female piston rod
Magnet	with magnet
Ovoj	Aluminium
Povezava	M5x0.8
Serijska	ASQ series
Starting position	pressureless in the retracted position
Tesnilo	NBR
Min. delovni tlak [bar]	2
Vrsta	4
Batnica Ø [mm]	6
Max. delovni tlak [bar]	10
Stroke [mm]	10
Bat Ø [mm]	12
Max. temperaturno območje [°C]	70