

Datum: 01.06.2025



(slika je simbolična)

Cilinder z vodikom, delujoč v dveh smereh, bat Ø 32, hod 1000

Kategorija: [Rodless cylinders](#)

Šifra: **106334RIE**

Kratek opis

Piston rod-free cylinder, double-acting, Magnet, Piston Ø 32, Stroke 1000, G 1/4, Working pressure 1 - 8 bar, Temp. -10°C to 80°C

These double-acting cylinders can also be supplied with strokes greater than 5 m, providing the stroke length is approximately equal to the overall length. They are equipped with magnets as standard for indicating the position as well as pneumatic, adjustable end position cushioning. Limit switches and hydraulic shock absorbers can be mounted as add-on modules.

Suitable for filtered (50 µm), unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Cushioning	cushioned
Drnik (vodilo bata)	Anodised aluminium alloy
Ffunkcija	double-acting
Magnet	with magnet
Ohišje	Jacket made from anodised aluminium alloy
Povezava	G 1/4
Sealing bands	Stainless steel
Tesnilo	NBR (for speeds up to 1 m/s)
Min. delovni tlak [bar]	1
Max. stranska obremenitev [Nm]	2
Max. delovni tlak [bar]	8
Bat Ø [mm]	32
Max. temperaturno območje [°C]	80
Sila pri 6 bar [N]	420
Stroke [mm]	1000