

Datum: 02.05.2025



(slika je simbolična)

## Coaxial valve pneumat. actuated, single-acting NC, FKM, Rp 3/8

Kategorija: [Coaxial valve, single-acting - spring to close,FKM](#)

Šifra: **103735RIE**

### Kratek opis

Coaxial valve pneumat. actuated, single-acting, NC, nickel-plated brass, Temp. -20°C to 150°C, Control pressure 4.2-8 bar, Rp 3/8

2/2-way coaxial valves, specially designed for automated industrial plant engineering.

A low-price, compact, space-saving and reliable alternative to ball valves with a pneumatic rotary actuator.

These valves have a full bore and - owing to the optimised design - only minimal flow losses.

They are controlled by means of filtered compressed air.

### Tehnične Specifikacije

|                               |                                    |
|-------------------------------|------------------------------------|
| Min. delovna temperatura [°C] | -20                                |
| Navoj                         | Rp 3/8                             |
| Notranji deli                 | Nickel-plated brass                |
| Ohišje                        | Nickel-plated brass                |
| Povezava                      | NAMUR interface, direct: 2 x G 1/8 |
| Različica                     | single-acting - spring to close    |
| Tesnilo                       | FKM                                |
| Vgradni položaj               | Any                                |
| Vzmet                         | Stainless steel                    |
| Min. vodeni tlak [bar]        | 4.2                                |
| Max. vodeni tlak [bar]        | 8                                  |
| DN                            | 10                                 |
| Max. obratovalni tlak [bar]   | 10                                 |
| H [mm]                        | 46.0                               |
| L [mm]                        | 98.0                               |
| Max. delovna temperatura [°C] | 150                                |