

Datum: 30.04.2025



(slika je simbolična)

Coaxial valve pneumat. actuated, single-acting NC, NBR, Rp 3/4

Kategorija: [Coaxial valve, single-acting - spring to open, NBR](#)

Šifra: **103733RIE**

Kratek opis

Coaxial valve pneumat. actuated, single-acting, NC, nickel-plated brass, Temp. -20°C to 80°C, Control pressure 4.2-8 bar, Rp 3/4

2/2-way coaxial valves, specially designed for automated industrial plant engineering.

A low-price, compact, space-saving and reliable alternative to ball valves with a pneumatic rotary actuator.

These valves have a full bore and - owing to the optimised design - only minimal flow losses.

They are controlled by means of filtered compressed air.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Navoj	Rp 3/4
Notranji deli	Nickel-plated brass
Ohišje	Nickel-plated brass
Povezava	NAMUR interface, direct: 2 x G 1/8
Različica	single-acting - spring to close
Tesnilo	NBR
Vgradni položaj	Any
Vzmet	Stainless steel
Min. vodeni tlak [bar]	4.2
Max. vodeni tlak [bar]	8
Max. obratovalni tlak [bar]	10
DN	20
H [mm]	63.5
Max. delovna temperatura [°C]	80
L [mm]	135.0