

Datum: 02.05.2025



(slika je simbolična)

Dvojna Hitre spojke I.D. 7.2, G 1/2 notranji navoj

Kategorija: [Distributor, 2 quick disconnect coupl. DN 7.2, IT](#)

Šifra: **107261RIE**

Kratek opis

Distributor with 2 quick-connect couplings I.D. 7.2, Bright brass, G 1/2 IT, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C

1, 2 or 3-way distributor pieces made of brass with a bare metal surface, pre-assembled with quick disconnect coupling DN 7.2.

Available with threaded connection inside or outside or nipple for adaptation into an existing quick disconnect coupling DN 7.2 to DN 7.8.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Ohišje	Brass with a bare metal surface
Povezava	G 1/2 IT
Sestava distributerja	Brass with a bare metal surface, G 1/2 IT
Spojke	DN 7.2, brass with a bare metal surface, G 1/2 ET
Tesnilo	Industrial adhesives, medium strength
Varovaka	Industrial adhesives, medium strength
Max. obratovalni tlak [bar]	35
Višina [mm]	71.0
Premier [mm]	95.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100