

**Datum:** 18.05.2025



(slika je simbolična)

## **Dvojni nav. priklj. 245, Z.N./Z.N.,reduciran,R 1/2,R 3/8**

Kategorija: [Hexagon nipple 245, reducing, male/male](#)

Šifra: **113090RIE**

### **Kratek opis**

Double threaded nipple 245, ET/ET, red., R 1/2, R 3/8, oper. temp. -20 °C to 300 °C, black malleable cast iron, Hot-dip galvanised

Acc. to DIN EN 10242 (formerly DIN 2950)

The classic - and the most popular - screw fitting series for pipe construction.

These fittings are characterized by their high mechanical strength and surface quality to DIN 2444.

They are completely coated with a layer of pure zinc and are therefore suitable for drinking water

### **Tehnične Specifikacije**

|                                |                                                     |
|--------------------------------|-----------------------------------------------------|
| Min. temperaturno območje [°C] | -20                                                 |
| Material                       | Black malleable iron<br>B350-10, design<br>symbol A |
| Navoj 1                        | R 1/2                                               |
| Navoj 2                        | R 3/8                                               |
| Površina                       | Hot dip galvanised                                  |
| Standardni navoj               | acc. ISO 7-1                                        |
| Max. temperaturno območje [°C] | 300                                                 |