

Datum: 01.05.2025



(slika je simbolična)

## Elektr. Tlačni pretvornik, 0 - 16 bar, G 1/2, CrNi jeklo 1.4571

Kategorija: [Pressure transmitter \(CrNi steel 1.4571\), S-20](#)

Šifra: **102732RIE**

### Kratek opis

Electr. pressure transducer, general industrial applications, Non-linearity 0.25%, Meas. range 0-16 bar, G 1/2, CrNi steel 1.4571

Pressure transmitters, very high precision, in CrNi steel, for complex measurement tasks in the process industry as well as research and development.

Applications: Low temperature or outdoor applications, extreme shock loads and vibration levels, corrosive media in the chemical industry.

Compatible with all internationally established process connections.

### Tehnične Specifikacije

|                              |                                                                             |
|------------------------------|-----------------------------------------------------------------------------|
| Min. sobna temperatura [°C]  | -30                                                                         |
| Min. temperatura medija [°C] | -30                                                                         |
| Deli v kontaktu z medijem    | CrNi-steel 1.4571<br>With right-angle connector acc. to DIN EN 175301-803 A |
| Električni priključek        | IP 65 acc. to EN 60529                                                      |
| IP zaščita                   | G 1/2                                                                       |
| Navoj                        | up to 0.25% of span                                                         |
| Nelinearnost                 | CrNi-steel 1.4571                                                           |
| Ohišje                       | DC 8 ... 36 V                                                               |
| Operativna napetost          | Positive pressure                                                           |
| Spodnja/Zgornja meja območja | S-20                                                                        |
| Vrsta                        | 4 - 20 mA, 2-wire                                                           |
| izhodni signal               | 16                                                                          |
| Merilno območje max. bar     | 100                                                                         |
| Max. sobna temperatura [°C]  | 100                                                                         |
| Max. temperatura medija [°C] | 100                                                                         |