

Datum: 01.05.2025



(slika je simbolična)

Elektr. Tlačni pretvornik, 0 - 25 bar, G 1/2, CrNi jeklo 1.4571

Kategorija: [Pressure transmitter \(CrNi steel 1.4571\), S-20](#)

Šifra: **102733RIE**

Kratek opis

Electr. pressure transducer, general industrial applications, Non-linearity 0.25%, Meas. range 0-25 bar, G 1/2, CrNi steel 1.4571

Pressure transmitters, very high precision, in CrNi steel, for complex measurement tasks in the process industry as well as research and development.

Applications: Low temperature or outdoor applications, extreme shock loads and vibration levels, corrosive media in the chemical industry.

Compatible with all internationally established process connections.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-30
Min. temperatura medija [°C]	-30
Deli v kontaktu z medijem	CrNi-steel 1.4571 With right-angle connector acc. to DIN EN 175301-803 A
Električni priključek	IP 65 acc. to EN 60529
IP zaščita	G 1/2
Navoj	up to 0.25% of span
Nelinearnost	CrNi-steel 1.4571
Ohišje	DC 8 ... 36 V
Operativna napetost	Positive pressure
Spodnja/Zgornja meja območja	S-20
Vrsta	4 - 20 mA, 2-wire
izhodni signal	25
Merilno območje max. bar	100
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100