

Datum: 30.04.2025



(slika je simbolična)

Filter»FUTURA«Kov. pos.5 µm, Vel. 4, G1, Pol avto.

Kategorija: [Filter with metal bowl and sight glass](#)

Šifra: **156555RIE**

Kratek opis

Filter »FUTURA« with metal container and viewing tube, 5 µm, Size 4, G 1, 1.5 - 16 bar, Temp. -10 °C to 50 °C, Semi-automatic

Filters with excellent flow rates in modern design.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Cellpor (PE)
Merjenje pretoka	At P ₂ = 6 bar and pressure drop Δ _p = 1 bar
Navoj	G 1
Odtok kondenzata	Semi-automatic
Ohišje	PA66 GF60
Posoda	Metal container with viewing tube
Priključni navoj	Material: Die-cast zinc
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Tesnilo	NBR
Min. vhodni tlak [bar]	1.5
Velikost	4
Rang filtra [µm]	5
Max. vhodni tlak [bar]	16
Max. temperaturno območje [°C]	50
C [mm]	58.0
A [mm]	85.0
B [mm]	247.0
Pretok [l/min]	8000