

Datum: 05.05.2025



(slika je simbolična)

Filter»G«,PC zbir.,Zaščitna kletka,5 µmVel. 400G 1/2

Kategorija: [Filter with polycarbonate bowl, bowl guard](#)

Šifra: **116407RIE**

Kratek opis

Filter »G« PC container, Protective cage, Mounting bracket,
5 µm, Size 400, G 1/2, Input pres. max 10 bar, Working pres.
1.5-9 bar
Centrifugal separators with a sintered filter element.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1/2
Odtok kondenzata	Fully-automatic
Ohišje	Die-cast aluminium
Posoda	Polycarbonate container with protective cage
Serijska	G
Tesnilo	NBR
Min. delovni tlak [bar]	1.5
Rang filtra [µm]	5
Max. delovni tlak [bar]	9
Max. vhodni tlak [bar]	10
C [mm]	25.0
A [mm]	68.0
Max. sobna temperatura [°C]	70
Max. temperatura medija [°C]	70
D [mm]	166.5
B [mm]	191.5
Velikost	400
Pretok [l/min]	4900