

Datum: 01.05.2025



(slika je simbolična)

Filter reg.»FUTURA« Kov. Vel.2, G 1/2, 0.1-2 bar, Avt.Kategorija: [Filter regulator with metal bowl and sight glass](#)Šifra: **151857RIE****Kratek opis**

Filter regulator »FUTURA«, with metal container, Viewing tube, Pressure gauge, 5 µm, Size 2, G 1/2, Control range 0.1-2 bar, Fully
Filter regulators with excellent flow rates in modern design.
The regulator knob can be latched and locked.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Cellpor (PE)
Membrane	NBR
	At $P_1 = 10$ bar, $P_2 = 6.3$
Merjenje pretoka	bar and pressure drop
	$\Delta p = 1$ bar
Navoj	G 1/2
Odtok kondenzata	Fully-automatic
Ohišje	PA66 GF60
Posoda	Metal container with viewing tube
Priključni navoj	Material: Die-cast zinc
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Tesnilo	NBR
Min. krmilno območje [bar]	0.1
Min. vhodni tlak [bar]	1.5
Max. krmilno območje [bar]	2
Velikost	2
Zaslon manometra max. [bar]	2.5
Rang filtra [µm]	5
Max. vhodni tlak [bar]	16
Max. temperaturno območje [°C]	50
A [mm]	63.0
C [mm]	110.0
B [mm]	277.0
Pretok [l/min]	5200