

Datum: 02.05.2025



(slika je simbolična)

Filter reg.»FUTURA« PC, Vel. 4, G 1, 0.5-10 bar, Pol avto.Kategorija: [Filter regulator, polycarbonate bowl, bowl guard](#)Šifra: **151782RIE****Kratek opis**

Filter regulator »FUTURA«, with PC container, Protective cage, Pressure gauge, 5 µm, Size 4, G 1, Control range 0.5-10 bar, Semi
Filter regulators with excellent flow rates in modern design.
The regulator knob can be latched and locked.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Cellpor (PE)
Membrane	NBR
Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1
Odtok kondenzata	Semi-automatic
Ohišje	PA66 GF60
Poraba zraka	Yes
Posoda	Polycarbonate container with protective cage
Priključni navoj	Material: Die-cast zinc
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Tesnilo	NBR
Min. krmilno območje [bar]	0.5
Max. notranja poraba zraka	1.5 l/min (depending on secondary pressure)
Min. vhodni tlak [bar]	1.5
Velikost	4
Rang filtra [µm]	5
Max. krmilno območje [bar]	10
Max. vhodni tlak [bar]	16
Zaslon manometra max. [bar]	16
Max. temperaturno območje [°C]	50
A [mm]	85.0
C [mm]	137.0
B [mm]	326.0
Pretok [l/min]	13000