

Datum: 05.05.2025

**Filter reg. »multifix«5 µmVel.1,G 1/4, 0.5 - 10 bar**

(slika je simbolična)

Kategorija: [Filter regulator with polycarbonate bowl](#)Šifra: **100470RIE****Kratek opis**

Filter regulator »multifix«, PC container, press. gauge, 5 µm, Size 1, G 1/4, Input pressure max. 16 bar, Control range 0.5-10 bar

Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator.

The pressure setting can be locked by pushing the button down.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6,3$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 1/4
Odtok kondenzata	Semi-automatic
Ohišje	Die-cast zinc
Posoda	Polycarbonate container
Serija	multifix
Tesnilo	NBR
Vzmet pokrova motorja	POM-brass
Min. krmilno območje [bar]	0.5
Velikost	1
Rang filtra [µm]	5
DN	6
Max. krmilno območje [bar]	10
Max. vhodni tlak [bar]	16
Zaslon manometra max. [bar]	16
A [mm]	47.8
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
C [mm]	67.0
D [mm]	125.1
B [mm]	192.1
Pretok [l/min]	1600