

Datum: 11.05.2025



(slika je simbolična)

Filter regulator »GA«, Kovinska posoda, 5 µm, Velikost 600, G 1

Kategorija: [Filter regulator with metal bowl, sight glass](#)Šifra: **178481RIE**

Kratek opis

Filter regulator »GA«, with metal container, Viewing tube, Mounting bracket, 5 µm, Size 600, G 1, Input pressure max. 10 bar

Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator. The pressure setting can be locked by pushing the button down.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-5
Merjenje pretoka	At $P_1 = 8 \text{ bar}$, $P_2 = 6 \text{ bar}$ and pressure drop $\Delta_p = 1 \text{ bar}$
Navoj	G 1
Odtok kondenzata	Semi-automatic
Ohišje	Die-cast aluminium
Posoda	Metal container with viewing tube
Serija	GA
Tesnilo	NBR
Vzmet pokrova motorja	Anodised aluminium
Min. krmilno območje [bar]	1.5
Rang filtra [µm]	5
Max. krmilno območje [bar]	9
Max. vhodni tlak [bar]	10
Max. temperaturno območje [°C]	70
A [mm]	100.0
C [mm]	131.5
D [mm]	205.0
B [mm]	336.5
Velikost	600
Pretok [l/min]	6000