

Datum: 08.05.2025



(slika je simbolična)

Filter regulator iz nerjevečega jekla, 1.4404, G 1/2, 1 - 15 bar

Kategorija: [Stainless steel filter regulators 1.4404](#)

Šifra: **101208RIE**

Kratek opis

Stainless steel filter regulator, 1.4404, with secondary venting (reversible), incl. press. gauge, G 1/2, Control range 1 - 15 bar

Stainless steel filter regulators with self-relieving (not for liquid media) containing no non-ferrous metals for use in the food processing, chemical, mining, plant construction and special machinery industries as well as in the medical technology.

Tehnične Specifikacije

Membrane	PTFE on NBR-carrier
Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 5$ bar and pressure drop $\Delta p \leq 1$ bar
Navoj	G 1/2
Odtok kondenzata	Manual drain valve
Ohišje	Stainless steel 1.4404 (AISI 316L)
Tesnilo	FKM
Min. krmilno območje [bar]	1
Max. krmilno območje [bar]	15
Max. vhodni tlak [bar]	30
Rang filtra [μ m]	50
Max. sobna temperatura [°C]	60
A [mm]	80.0
C [mm]	127.0
Max. temperatura medija [°C]	130
B [mm]	260.0
Pretok	2500 l/min