

Datum: 05.05.2025

**Filter regulator »multifix«, 40 µm, Velikost 5, G 1, 0.5 - 10 bar**

(slika je simbolična)

Kategorija: [Filter regulator with polycarbonate bowl](#)Šifra: **100486RIE****Kratek opis**

Filter regulator »multifix«, PC container, press. gauge, 40 µm, Size 5, G 1, Input pressure max. 16 bar, Control range 0.5-10 bar

Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator.

The pressure setting can be locked by pushing the button down.

Tehnične Specifikacije

Max. notranja poraba zraka	0,5 l/min (depending on secondary pressure) At $P_1 = 10$ bar, $P_2 = 6,3$ bar and pressure drop $\Delta p = 1$ bar
Merjenje pretoka	G 1
Navoj	Semi-automatic
Odtok kondenzata	Aluminium
Ohišje	Yes
Poraba zraka	Polycarbonate container
Posoda	multifix
Serijska	NBR
Tesnilo	POM-brass
Vzmet pokrova motorja	
Min. krmilno območje [bar]	0.5
Velikost	5
Max. krmilno območje [bar]	10
Max. vhodni tlak [bar]	16
Zaslona manometra max. [bar]	16
DN	25
Rang filtra [µm]	40
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
A [mm]	100.0
C [mm]	128.0
D [mm]	253.8
B [mm]	381.8
Pretok [l/min]	15000