

Datum: 07.05.2025



(slika je simbolična)

Filter regulator »multifix-mali«, Kovinska posoda, G 1/4, 0.5-10Kategorija: [Filter regulator with metal bowl, pressure gauge](#)Šifra: **100356RIE****Kratek opis**

Filter regulator »multifix-mini«, Metal container, press. gauge, 5 µm, G 1/4, Input pressure max. 16 bar, Control range 0.5-10 bar

Reversible diaphragm pressure regulators, independent of inlet pressure, with secondary ventilation, in combination with a centrifugal separator. The pressure setting can be locked by pressing in the handwheel.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1/4
Odtok kondenzata	Semi-automatic
Ohišje	Die-cast zinc
Posoda	Metal container
Serijska	multifix-mini
Tesnilo	NBR
Vzmet pokrova motorja	POM-brass
Min. krmilno območje [bar]	0.5
DN	5
Rang filtra [µm]	5
Max. krmilno območje [bar]	10
Max. vhodni tlak [bar]	16
Zaslon manometra max. [bar]	16
A [mm]	40.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
C [mm]	63.0
D [mm]	99.0
B [mm]	162.0
Pretok [l/min]	1450