

Datum: 01.05.2025



## Filter regulator »Stinard-mali«, Kovinska posoda, 5 µm, G 1/4

(slika je simbolična)

Kategorija: [Filter regulator with metal bowl](#)Šifra: **100784RIE**

### Kratek opis

Filter regulator »Standard-mini« with metal container incl. press. gauge and control cabinet nut, 5 µm, Size 0, G 1/4, 0.5-10 bar  
Compact, reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator. The pressure setting can be locked by pushing the knob down.

### Tehnične Specifikacije

|                              |                                                                      |
|------------------------------|----------------------------------------------------------------------|
| Merjenje pretoka             | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj                        | G 1/4                                                                |
| Odtok kondenzata             | Manual                                                               |
| Ohišje                       | Die-cast zinc, painted silver                                        |
| Posoda                       | Metal container                                                      |
| Serijska                     | Standard-mini                                                        |
| Tesnilo                      | NBR                                                                  |
| Vzmet pokrova motorja        | POM-brass                                                            |
| Min. krmilno območje [bar]   | 0.5                                                                  |
| DN                           | 5                                                                    |
| Rang filtra [µm]             | 5                                                                    |
| Max. krmilno območje [bar]   | 10                                                                   |
| Zaslon manometra max. [bar]  | 16                                                                   |
| Max. vhodni tlak [bar]       | 25                                                                   |
| A [mm]                       | 40.0                                                                 |
| Max. sobna temperatura [°C]  | 60                                                                   |
| Max. temperatura medija [°C] | 60                                                                   |
| C [mm]                       | 65.0                                                                 |
| D [mm]                       | 98.5                                                                 |
| B [mm]                       | 163.5                                                                |
| Pretok [l/min]               | 350                                                                  |