

Datum: 02.05.2025



(slika je simbolična)

Filter regulator »variobloc« z zaščitno kletko, Velikost 1, G 3/8

Kategorija: [Filter regulator with PC bowl and bowl guard](#)Šifra: **124782RIE**

Kratek opis

Filter regulator »variobloc«, PC container, Protective cage and pressure gauge, Size 1, G 3/8, Input pressure max. 16 bar

Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator.

The pressure setting can be locked by pushing the knob down.

Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

Tehnične Specifikacije

Membrane	NBR
Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 3/8
Odtok kondenzata	Manual
Ohišje	Die-cast zinc
Posoda	Polycarbonate container with protective cage variobloc
Serija	NBR
Tesnilo	POM
Vzmet pokrova motorja	0.5
Min. krmilno območje [bar]	1
Velikost	10
Max. krmilno območje [bar]	10
Zaslon manometra max. [bar]	16
Max. vhodni tlak [bar]	40
Rang filtra [μ m]	48.0
A [mm]	50
Max. sobna temperatura [°C]	50
Max. temperatura medija [°C]	50
C [mm]	68.0
B [mm]	203.0
Pretok [l/min]	3000